





PACKAGE



TECHNICAL CHARACTERISTICS



AVAILABLE BLADES


























- Maximum length of cut 90 cm (35 1/2").
- Maximum depth of cut 45 mm (1 3/4") in single pass; 60 mm (2 3/8") in double pass.
- Diamond blade: max Ø 200 mm (8"); min Ø180 mm (7").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump.
- Sliding bar and pivots in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.

393N 090EU

- Re-adjustable aluminum sauare.
- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings. MODEL SPECIFICATIONS
- Tiling legs.
- Motor held by galvanized metal frame.
 - Tilting movement (0-47°) for 45° angle cut (jolly).
 - Available accessories: extra side square, self-standing side bench with rollers, 4 wheels + 2

• Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.

• Supplied with Ø 200 mm (8") continual crown diamond disc for ceramic tiles, user manual, keys kit, dressing stone.

2800

3360

3360

200 mm

200 mm


200 mm

8"

8"

393N 090BR 8024648091031 393N 090US 8024648089410

8024648089397



Single-phase

Single-phase

Single-phase





230 V 50 Hz

230 V 60 Hz

110 V 60 Hz



0,9 HP / 0,65 kW

0,9 HP / 0,65 kW 0,9 HP / 0,65 kW



 \odot

2800

3360

3360