


BRIDGE AND JOB SITE SAW MACHINES



AVAILABLE BLADES




ACCESSORIES



PACKAGE



TECHNICAL CHARACTERISTICS



- For cutting granite, marble, porcelain, single and double fired, bricks, cement etc...
- Maximum length of cut 220 cm (86 2/8").
- Maximum depth of cut 90 mm (3 1/2") in single pass; 125 mm (4") in double pass.
- Diamond blade max Ø 360 mm (14"); min Ø 300 mm (12").
- Plunge cut and adjustable cutting depth.
- Heavy duty water pump and jet nozzles provide superior blade cooling.
- Water jet near to the cutting point for an optimal cooling.
- Pivoting blade guard remains parallel with tile to ensure maximum cutting depth.
- Cast and extruded aluminum framework.
- Re-adjustable square for long lasting precision.
- Easy-to-remove polypropylene tank for easy cleaning. Capacity: 38 lt (10 Gal).

- Sliding motor assembly with galvanized steel housing provided with 4 pulleys (double internal bearings each).
- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- Equipped with the motor feed system with wheel kit.
- Telescopic legs provided with double safety device and wheels kit.
- Equipped with: diamond disc Ø 350 mm (14") for porcelain tiles, wheel kit feed, wheels kit for easy transport, keys kit, user manual.
- Wide range of accessories available.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	Motor	M	Motor	Motor	Blade	Blade	
<b>223MS200EU</b>	8024648096289	1	230 V 50 Hz	● 2P+T / 16A	Single-phase	3 HP / 2,2 kW	2800	300 mm	12"	2800
<b>223MS200V400</b>	8050532005518	1	400 V 50 Hz	● 3P+T+N / 16A	Three-phase	3 HP / 2,2 kW	2800	300 mm	12"	2800
<b>223MS200BR</b>	8024648096265	1	230 V 60 Hz	● 2P+T / 16A	Single-phase	3 HP / 2,2 kW	3360	300 mm	12"	3360
<b>223MS200US</b>	8024648096302	1	110 V 60 Hz	● 2P+T / 16A + UL	Single-phase	2 HP / 1,5 kW	3360	300 mm	12"	3360

Model	Blade	Blade	Blade	Blade	Blade	Blade	Blade	Blade	Blade	Blade			
<b>SMS 220</b>	350 mm 300 mm	14" 12"	90 mm 60 mm	3 1/2" 2 3/8"	50 mm 45 mm	2" 1 3/4"	220 cm 86 2/8"	∞	155x155 cm 61"x 61"	270x85xh 85 cm 106"x33 1/2"xh 33 1/2"	120 Kg 264.6 lbs	275x85xh 92 cm 108 1/4"x33 1/2"xh 36 1/5"	208 Kg 458.6 lbs

