




AVAILABLE BLADES




OPTIONAL



PACKAGE



TECHNICAL CHARACTERISTICS



- For cutting single-double fired and porcelain. Straight cuts and 45° bevel (Jolly).
- Unlimited size of cut.
- Maximum thickness of cut: 20 mm (13/16") in single pass; 40 mm (1 5/8") in double pass.
- Maximum disc: Ø 150 mm (6").

- Blade is cooled through immersion in the water reservoir.
- Tilting table for bevel cuts from 0° to 47°.
- Supplied with: continuous rim blade for tiles Ø 150 mm (6"), key kit, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Disc	Disc	
378 98	8024648003621	1	230 V 50/60 Hz	Single-phase	0,5 HP / 0,37 kW	2800/3360	150 mm	6"	2800/3360
378 USA	8024648008824	1	110 V 60 Hz	Single-phase	0,33 HP / 0,24 kW	3360	150 mm	6"	3360
378 GB	8024648008800	1	110 V 50 Hz	Single-phase	0,33 HP / 0,24 kW	2800	150 mm	6"	2800

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc	Thickness	Depth	Angle	Angle	Angle	Dimensions	Weight	Dimensions	Weight
SUPERECO 98	150 mm 6"	20 mm 13/16"	30 mm 1 3/16"	∞	∞	∞	45x42xh 22 cm 17 3/4"x16 1/2"xh 8 5/8"	11 Kg 24 lbs	50x45xh 30 cm 19 5/8"x17 3/4"xh 11 7/8"	12 Kg 26 lbs

