

BULLDOG ADVANCED WITH WHEEL KIT FEED




MACHINES FOR SPECIAL JOBS

AVAILABLE BLADES



TECHNICAL CHARACTERISTICS



ACCESSORIES



PACKAGE



- For bullnosing and beveling. Create 1/2 Bullnose, full bullnose, 45° bevel (Jolly) on: marble, granite, porcelain, single and double fired.
- Provided with wheel feed kit.
- Maximum length of shaping: 120 cm (47 1/4").
- Minimum tile width: 4 cm (1 1/2"). Maximum tile width: 60 cm (23 5/8").
- Maximum depth of shaping/radius half bullnose: 30 mm (1 3/16").
- Maximum depth of shaping full bullnose: 22 mm (7/8"); wheel radius: 11 mm (7/16").

- Optional: external tank + pump kit.
- Three levels of finishing: rough, finished, polished.
- Gear ratio of motor to wheel 1 ÷ 1.6. Drive belt type poly V.
- Heavy duty water pumps provides superior wheel cooling.
- Supplied with: milling bullnose wheel radius 10 mm (3/8"), universal table, key kit with wrench, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	Motor	Motor	Motor	Wheel	Wheel	Wheel
427AVOL 230	8024648079701	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	r.10 mm	r. 3/8"	4480
427AVOL 60	8024648079718	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3660	r.10 mm	r. 3/8"	5370
427AVOL USA	8024648079695	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3660	r.10 mm	r. 3/8"	5370
427AVOL GB	8024648079671	1	110 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	r.10 mm	r. 3/8"	4480

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Profile	Wheel	Wheel	Wheel	Wheel	Wheel	Wheel	Weight	Dimensions	Weight				
BULLDOG ADV WITH WHEEL KIT FEED		30 mm	1 3/16"	30 mm	1 3/16"	—	—	120 cm 47 1/4"	60 cm 23 5/8"	200x85xh 100 cm 79"x 33"xh 40"	99 Kg 218.3 lbs	250x100xh 135 cm 98"x40"xh 53"	144 Kg 317.5 lbs	
		20 mm	3/4"	20 mm	3/4"	—	—							
		15 mm	5/8"	15 mm	5/8"	—	—							
		10 mm	3/8"	10 mm	3/8"	—	—							
		8 mm	5/16"	8 mm	5/16"	—	—							
		V45°	—	—	15 mm	5/8"	—							—
		90°	30 mm	1 3/16"	—	—	—							—
	11 mm	7/16"	22 mm	7/8"	—	—								

