





HOLE CUTTING MACHINES AND BITS

TECHNICAL CHARACTERISTICS



PACKAGE



- For pre-drilling holes on: marble, porcelain, single and double fired, granite, glass, etc....
- Clearance between the center of the drills and the frame: 35 cm - 14" (see image A).
- Perform drilling also on installed floors.
- Put it on the tiles directly (by removing the tank) for drilling tiles of any size.
- Maximum thickness of tile: 30 mm (1 3/16").
- Maximum wheel: Ø 120 mm (4 3/4"); smallest: Ø 4 mm (5/32").
- Variable speed from 260 to 1050 rpm.

- Through bit cooling via pump.
- Tile holder with splash guard.
- Quick Change core drills.
- Exclusive rotating tile support plates (patented).
- Supplied with: tile support plates, hex keys, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.									
205F EU	8050532000834	1	230 V 50/60 Hz	Single-phase	1,5 CV / 1,1 kW	243-854	•	-	260/1050

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model								
FORASPEED	4 - 120 mm 5/32" - 4 3/4"	30 mm 1 3/16"	35 cm 14"	∞	65x43xh 48 cm 25 1/2"x17"xh 19"	21,1 Kg 46.5 lbs	76x54xh 65 cm 30"x21 1/4" x 25 1/2"	26,3 Kg 58 lbs

