

MOLOSSO AND MASTINO



MOLOSSO



MASTINO

VIBRATORS AND ELECTRICAL BARS

MOLOSSO TECHNICAL CHARACTERISTICS



65x53 cm



36 ROLLERS



TELESCOPIC HANDLE



WOODEN CASE



OVERLAPABLE PALLETS

MOLOSSO PACKAGE

MASTINO TECHNICAL CHARACTERISTICS



300 W



49x56 cm



36 ROLLERS



SPEED SELECTOR



TELESCOPIC HANDLE

MASTINO PACKAGE



CARTON BOX

- Both designed for laying tiles in mud bed, using the vibration method.
- MOLOSSO is designed for tiles 60x60 cm (23 5/8" x 23 5/8") of 20 mm (3/4") thickness.
- MOLOSSO has a sturdy structure and a 0,9 HP - 0,66 kW motor; net weight: 85 Kg (187 lbs).
- MASTINO is equipped with transformer from 230/110 Volt to 42 Volt.
- MOLOSSO: five vibration intensities
MASTINO: three vibration intensities speeds: 4000/6500/8600 rounds/min.

- Both are equipped with 36 rollers (9 rows of 4 rollers each) Ø 55 mm (2"). MOLOSSO has longer rollers for a larger vibration area.
- Both have a telescopic handle.
- The high vibration frequency enables perfect levelling of the tiles and ensures the full bond of the mud to the tile.
- Steel roller holder.

MOLOSSO MODEL SPECIFICATIONS

Part No.							
350R9 UE	8024648093820	230V 50/60 Hz	Single-phase	0,9 CV / 0,66 kW	2800 / 3360	65x53 cm 25 1/2" x 21"	—
350R9 US	8024648094094	110 V 60 Hz		0,9 CV / 0,66 kW	3360		—
350R9 GB	8024648096029	110 V 50 Hz		0,9 CV / 0,66 kW	2800		—

MOLOSSO DIMENSIONS AND WEIGHT

Part No.							
MOLOSSO	1	85 Kg	187.4 lbs	90x72x h 63 cm	35 1/2"x28 1/8"x h 25"	99 Kg	218,26 lbs

MASTINO MODEL SPECIFICATIONS

Part No.							
349	8024648004314	230/42V 50/60Hz	Single-phase	300 W	10000/12000	49x56 cm 19 1/4"x22"	•
349 US	8024648089670	110/42V 60Hz					•
349 GB	8024648009425	110/42V 50Hz					•

MASTINO DIMENSIONS AND WEIGHT

Part No.							
MASTINO	1	56,6 Kg	124.8 lbs	60x60xh 34 cm + 100x50xh 12 cm	23"x23"xh 13 1/2" + 40"x20"xh 5"	59 Kg	130.1 lbs

