




TERRANOVA

DOBERMANN

TERRANOVA TECHNICAL CHARACTERISTICS



DOBERMANN TECHNICAL CHARACTERISTICS



PACKAGE



- For laying tiles in mud bed, using the vibration method.
- The high vibration frequency (8600 rounds/min.) enables perfect levelling of the tiles and ensures the full bond of the mud to the tile.
- Telescopic handle.
- Three vibration speeds: 4000/6500/8600 rounds/min.

- Roller: Terranova with 44 rollers (11 rows of 4 rollers each) Ø 40 mm (1 5/8").
- Dobermann with 36 rollers (9 rows of 4 rollers each) Ø 40 mm (1 5/8").
- Steel roller holder.
- Supplied with: transformer from 230/110 Volt to 42 Volt.

TERRANOVA MODEL SPECIFICATIONS

Part No.							
<b>105</b>	8024648004321	230/42V 50/60Hz	Single-phase	200 W	8600/10300	47x52 cm 18 1/2"x20 1/2"	•
<b>105USA</b>	8024648009456	110/42V 50/60Hz					•

TERRANOVA DIMENSIONS AND WEIGHT

Part No.				
<b>TERRANOVA</b>	1	47 Kg   103.6 lbs	80x50xh 30 cm	31 1/2"x20"xh 11 7/8"   49 Kg   108 lbs

DOBERMANN MODEL SPECIFICATIONS

Part No.							
<b>107</b>	8024648004345	230/42V 50/60Hz	Single-phase	200 W	8600/10300	39x52 cm 15 3/8"x20 1/2"	•
<b>107USA</b>	8024648009517	110/42V 50/60Hz					•

DOBERMANN DIMENSIONS AND WEIGHT

Part No.				
<b>DOBERMANN</b>	1	42 Kg   92.6 lbs	80x50xh 30 cm	31 1/2"x20"xh 11 7/8"   44 Kg   97 lbs

