IPERTITINA PLUS







 Single rotating head for polishing and sanding surfaces, for restoring finish to marble and granite floors, for sanding wood floors, for smoothing of mortar base, for cleaning and treatment of Terracotta, for power grouting floors

PREDISPOSED FOR SUTION LEGS WITH WHEELS TELESCOPI I FGS

- The oscillating motor assembly maximizes maneuverability and optimizes tools effectiveness.
- Telescopic handle with adjustable tilt.

REDUCER

- Magnetic Quick Change attachments, add on ballasts for extra weight, extra large water/liquid tank and dust sealing skirt are some of the features available.
- Double suction ports for dust extraction.
- \bullet Geared wheel for satellite tools available (increases RPM by a factor of 5x).
- Available in two versions 110/255 revolutions/min (135/300 for 60 Hz versions).
- \bullet Accomodates attachements with diameters from 49 cm (19 $_{1/4}^{\prime\prime})$ to 60 cm (23 $_{5/8}^{\prime\prime}).$
- Supplied with: hex key kit, user and maintenance manual.

MODEL SPECIFICATIONS												
Part No.			N	M		a de la compactación de la compa						
108 BIL55	8024648068569	1	230 V 50 Hz	Single-phase	3 HP / 2,2 kW	1400	55					
108 BIL110	8024648000767	1	230 V 50 Hz	Single-phase	3 HP / 2,2 kW	2800	110					
108 BIL110H6	8024648053718	1	230 V 60 Hz	Single-phase	3 HP / 2,2 kW	3360	132					
108 BIL110GB	8024648000781	1	110 V 50 Hz	Single-phase	2,5 HP / 1,8 kW	2800	110					

DIMENSIONS AND WEIGHT

Model					\$								
IPERTITINA PLUS	1	64 Kg 141 l	bs 55x130xh 120 cm	21″x51″xh 47″	81x68x h 64cm	32″x26″xh 25″	74 Kg	163 lbs					

TELESCOPI HANDLE

RAIMONDI