









R.L.S. WEDGE (SUITABLE FOR ALL CLIPS)

- Robust and reusable;
- Suitable for all clips of R.L.S. Wedge/Clip system;


Dimensions: 92x23xh 17 mm (3 5/8"x29/32"xh 43/64")

Part No.			Description				
180CUNEO100	8024648067944	12	RLS Wedge - 100 pz pieces bag	60x40xh31 cm	23 5/8"x15 3/4"x h 12 1/4"	11,7 Kg	25.8 lbs
180CUNEO250	8024648011947	6	RLS Wedge - 250 pz pieces bag	60x40xh31 cm	23 5/8"x15 3/4"x h 12 1/4"	11,7 Kg	25.8 lbs
180CUNEO500	8024648011954	3	RLS Wedge - 500 pz pieces bag	60x40xh31 cm	23 5/8"x15 3/4"x h 12 1/4"	11,7 Kg	25.8 lbs
180CUNEO1000	8024648069818	1	RLS Wedge - 1000 pz pieces bag	30x40xh42 cm	11 1/2"x16"xh 16 1/2"	8,2 Kg	16.3 lbs
180CU500SE	8024648072603	2	RLS Wedge - 500 pieces plastic bucket	62x42xh36 cm	25 1/2"x16 1/2"xh 14"	10,8 Kg	23.8 lbs

R.L.S. WEDGE/CLIP - TILES CHIPPING (AND SCRATCHING) PREVENTING PLATFORM + MULTI-SIZE SPACER









COMPATIBILITY WITH CLIPS R.L.S.

R.L.S.	R.L.S.	R.L.S.	R.L.S.	R.L.S.	R.L.S.
HD	High Thickness	0,5mm	1 mm	3D	VITE
•	•	-	_	•	




- Anti-chipping and anti-scratch platform to be used in combination with RLS wedge/clip system.
 The platform can be reused over and over again, both as anti-chipping and anti-scratch element and It avoid potential damage during installation of tiles characterized by a particularly delicate top
- The platform performs two functions at the same time: Anti-chipping since it prevents the stems of the RLS clip to touch the edge of the tile during wedge • It increases the joint size of 0.5 mm (0.019 inches). This is in order to perform the anti-chipping insertion thanks to a dedicated L-shaped tab;
- Anti-scratch since the wedge does not touch the tile but slides on the platform instead.
- Furthermore, the platform can also be used as a removable and reusable multi-size-spacer. In fact, 3 sides are designed to perform this function and the create respectively joints sided 1.5 mm, 2 mm and 3 mm (1/16", 5/64", 1/8").
- multi-size-removable-spacer.
- The use of the platform keeps the performance of the clips unaltered in terms of maximum and minimum thickness of the tiles to be leveled.
- It is recommended to perform the final removal phase with a hammer.
- Comes into plastic bucket for convenient storage.


RLS: TILES CHIPPING (AND SCRATCHING) PREVENTING PLATFORM AND MULTI-SIZE SPACER

Part No.			Description	Pieces per Bag	‡		کے	
180AGS0250	8050532007437	4	Tiles chipping (and scratching) preventing platform and multi-size spacer	250	49x39xh 25 cm	19 1/4"x15 3/8"xh 10"	5 Kg	11 lbs









R.L.S. WEDGE/CLIP -TRACTION-ADJUSTABLE-PLIERS (MANUAL)











- Traction-adjustable pliers for tightening the wedge of the RLS Wedge/Clip system;
- For tiles with thickness from 3 to 20 mm (from 1/8" to 3/4");

- Available in floor version and wall version;
- The steel frame guarantees sturdiness and reliability.

R.L.S TRACTION-ADJUSTABLE-PLIERS (MANUAL)

Part No.			Description			2	
231N	8024648072627	4	Adjustable pliers for floor covering	32x32xh 8 cm	12 5/8"x12 5/8"xh 5/16"	2 Kg	4,4 lbs
231 NRIV	8024648072634	4	Adjustable pliers for wall covering	32x32xh 8 cm	12 5/8"x12 5/8"xh 5/16"	2 Kg	4,4 lbs

RAIMONDI raimondispa.com Q5